

MMA

10 > 200 A

GYSMI 200P

Ref. 030794



Aparat za zavarivanje sa inverter tehnologijom vođenom mikroprocesorom



Dinamika električnog luka je jedinstvena i revolucionarna na tržištu



Mogućnost zavarivanja svim vrstama elektroda: rutilnim, bazičnim, prohromskim i gusanim



Lak za rukovanje zahvaljujući maloj težini (5,0 kg) i malim dimenzijama

**MMA**

Neposredni start zahvaljujući niskom opterećenju napona

Konstantna snaga zavarivanja

Vrlo glatko topljenje zahvaljujući jednosmernoj struji

Neosetljivi na nestalnost napona ili dužinu luka

Veoma dobra prodornost i odlična stabilnost luka

**PREIMUĆSTVA:**

Hot Start: povećana snaga na početku

Anti sticking: sprečava lepljenje elektrode

Arc force: trenutno povećanje struje u teškoj situaciji za zavarivanje



Zaštita pri radu sa generatorima struje i od nestabilnosti pri snabdevanju (+/- 15%)

50/60hz	AM	I ₂ MMA	Ø1,6	Ø2,0	Ø2,5	Ø3,2	Ø4,0	Ø5,0	EN60974-1 (40°C)	U ₀	mm ²	cm/kg	Protected & compatible POWER GENERATOR (+/- 15%)	
									I _A (60%)	X% (I ₂ max)				
230V	32A	10 - 200A	62	50	47	45	30	21	120A	200A 20%	72V	10/25	14x18x27 / 5	7 kW 10 kVA

CE - EN 60974-1

MADE in FRANCE

www.gys.fr